



RLDB808-120-3

- Infrared Diode Laser Module
- 808 nm, 120 mW
- Focus Adjustable
- Dimension: $\varnothing 22 \times 65$ mm



Description

RLDB808 series of Diode Laser Modules has been designed as a small housing laser module solution. The modules body is made of black anodized aluminum, enclosing laser diode, lens, and driving electronics. RLDH808 series features a **focusable glass lens optic** with a locking mechanism and **incorporated 3 VDC driver** circuit.


Specifications

Parameter	Min.	Values Typ.	Max.	Unit
Peak Wavelength		808		nm
Optical Output Power		120		mW
Laser Class		3B		
Operating Voltage		DC 3		V
Operating Current			250	mA
Control		APC		
Standard Operating Distance		10		m
Focus		Adjustable		
Beam Character		Elliptical		
Elliptic Proportion	1:2.5			
Output Aperture Diameter		7		mm
Divergence		0.3		mrad
Optic		Glass lens, both sides AR coated		
Operating Temperature	-10		+40	°C
Storage Temperature	-40		+80	°C
Life Time	5000			hours
Material		black anodized aluminum		
Electrical Connection		connector plug		
Dimension (Dia. x W)		$\varnothing 22 \times 65$		mm
Weight		60		g





Outline Dimensions



All Dimensions in mm

Electrical Connection



Precautions

Mounting Instruction:

In order to maintain lifetime and stability of the laser diode it is essential to provide efficient heat management. For long time stable operation proper contact between laser module and heat sink is mandatory.

Safety Advice:

This laser module emits highly concentrated visible light which can be **hazardous to the human eye and skin**. It is classified as **CLASS 3B laser product** according to **IEC 60825-1** and **21 CFR Part 1040.10 Safety Standards**. Actual laser light emitted and precautions necessary strongly depend on mode of operation.