



SPL650-1W-105M

- Fiber-Coupled Laser Diode
- 658 nm, 1 W
- 105 μm Multimode Fiber



Description

SPL650-1W-105M is a red fiber-coupled laser diode, typically emitting at 658 nm with an output power of 1 W. It comes in a high heat load package with 105 μm multimode fiber and FC/PC connector.

Additional options such as alternative fiber connector or package are available on request..

Maximum Rating ($T_{\text{CASE}} = 25^{\circ}\text{C}$)

Parameter	Symbol	Values		Unit
		Min.	Max.	
Reverse Voltage	V_R		2.0	V
Operating Temperature	T_{OPR}	- 10	+ 40	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	- 40	+ 85	$^{\circ}\text{C}$
Soldering Temperature (max. 3s)	T_{SOL}		+ 260	$^{\circ}\text{C}$

Electro-Optical Characteristics ($T_{\text{CASE}} = 25^{\circ}\text{C}$)

Parameter	Symbol	Values			Unit
		Min.	Typ.	Max.	
Peak Wavelength	λ_P	650	658	665	nm
Spectral Width (FWHM)	$\Delta\lambda$		2.0		nm
Output Power	P_O		1		W
Threshold Current	I_{th}		0.4	0.6	A
Operating Current	I_F		1.4	1.6	A
Operating Voltage	V_F		2.4	2.8	V
Fiber Specification	Type	Multimode			
	Core	105			μm
	Numerical	0.22			
	Connector *	FC/PC			
	Length	80			cm



* optional: SC or SMA905




Electrical Connection

Pin Configuration*


PIN #	Function
1	LD Cathode
2	LD Anode

Bottom View



* subject to change

Outline Dimension



All dimensions in mm



Precautions

Safety

Caution: Laser light emitted from any laser diode may be harmful to the human eye. Avoid looking directly into the laser diode's aperture when the diode is in operation.

Note: The use of optical lenses with this laser diode will increase eye hazard



ESD Caution

Always do handle laser diodes with extreme care to **prevent electrostatic discharge**, the primary cause of unexpected diode failure. To prevent ESD related failures we strongly advise to always **wearing wrist straps**, and **grounding all applicable work surfaces**, when handling laser diodes



Operating Considerations

We strongly advise to only operate this laser diode with a current source. The current of a laser diode is an exponential function of the voltage across it. **Usage of current regulated drive circuits is mandatory.**

Laser diodes may be damaged by excessive drive currents or switching transients

It is advised, to operate the laser diode at the lowest temperature possible, and to never exceed maximum specifications as outlined in the datasheet. Device degradation will accelerate with increased temperature. **Proper heat sinking will greatly enhance stability and life-time of the laser diode.**

© All Rights Reserved

The above specifications are for reference purpose only and subjected to change without prior notice